WHAT IS CLAIMED IS:

	•	1 i 1	A		comprising:
		An ontical	Transcelver	manne	COHIDITATIVE.
1	1.	All Oblicar	H WITHOUT A OT	111000010,	00111P110111-0.

- 2 a housing;
- a plurality of components disposed at least partially within said housing, said
- 4 components including:
- 5 an optical transmitter;
- 6 an optical receiver; and
- 7 a power controller integrated circuit (IC) electrically coupled to at least one of
- 8 said plurality of components, where said power controller IC is configured to perform
- 9 power supply functions for said optical transceiver module and said power controller
- 10 IC includes multiple voltage regulators providing power to said components at two or
- 11 more voltages.
- 1 2. The optical transceiver module of claim 1, wherein at least one of said
- 2 multiple voltage regulators is a low drop-out voltage regulator configured to receive
- 3 an unregulated input voltage and configured to supply a regulated output voltage to at
- 4 least one of said components.
- 1 3. The optical transceiver module of claim 1, wherein at least one of said
- 2 multiple voltage regulators is a boost or buck regulator electrically coupled to at least
- 3 one of said components.
- 1 4. The optical transceiver module of claim 1, wherein said power controller IC
- 2 further includes a serial bus within said power controller IC.
- 1 5. The optical transceiver module of claim 4, wherein said multiple voltage
- 2 regulators are electrically coupled to said serial bus.
- 1 6. The optical transceiver module of claim 5, wherein said power controller IC
- 2 further comprises a serial interface electrically coupled to said serial bus.

- 1 7. The optical transceiver module of claim 6, wherein said components further
- 2 comprise a main controller electrically coupled to said serial interface, such that in use
- 3 said main controller can control at least one of said multiple voltage regulators.
- 1 8. The optical transceiver module of claim 5, wherein said voltage regulators are
- 2 individually addressable.
- 1 9. The optical transceiver module of claim 1, wherein at least one of said voltage
- 2 regulators includes an Avalanche Photo Diode (APD) voltage supply.
- 1 10. The optical transceiver module of claim 1, wherein at least one of said voltage
- 2 regulators is adjustable.
- 1 11. The optical transceiver module of claim 1, wherein said power controller IC
- 2 further includes a plurality of components selected from a group consisting of: an
- 3 analog to digital converter, a temperature sensor, a digital to analog converter, a logic
- 4 module, an inrush current limiter, and a processor management module.
- 1 12. The optical transceiver module of claim 1, wherein said components further
- 2 include a laser driver IC electrically coupled to said optical transmitter, and a post-
- 3 amplifier IC electrically coupled to said optical receiver.
- 1 13. The optical transceiver module of claim 1, wherein said components further
- 2 include a main controller IC electrically coupled to at least one of said components.
- 1 14. The optical transceiver module of claim 13, wherein said power controller IC
- 2 is electrically coupled to and controlled by said main controller IC.